



Automatic Fire Sprinkler Systems New Construction Matrix

September 2012 - 2009 I-Codes

For additional information contact: Fire Prevention Division (785) 832-3174 <u>cking@lawrenceks.org</u>

Lawrenceks.org/fire_medical/prevention

Building Safety Division (785) 832-7700 <u>buildinginspections@lawrenceks.org</u> Lawrenceks.org/pds

Group A (Assembly) Occupancies Assembly Group A occupancy includes, among others, the use	
of a building or structure, or a portion thereof, for the	
gathering of persons for purposes such as civic, social or	
religious functions; recreation, food or drink consumption or	
awaiting transportation.	Automatic Fire Sprinkler System Required where the fire area:
A-1 Assemby, usually with fixed seating, intended for the	
production and viewing of the performing arts or motion	
pictures. This group includes:	1. Exceeds 12,000 square feet; or
Motion picture theaters	2. Has an occupant load of 300 or more; or
Symphony and concert halls	3. Is located on a floor other than a level of exit discharge serving such occupancies.
Theaters	4. Contains a multitheater complex.
A-2 Assembly, occupancies intended for food and/or drink	
consumption. This group includes:	1. Exceeds 5,000 square feet; or
Banquet Halls	2. Has an occupant load of 100 or more; or
Night clubs/bars	3. Is located on a floor other than a level of exit discharge serving such occupancies.
Restaurants	
A-3 Assembly, occupancies intended for worship, recreation	
or amusement and other assembly uses not classified	
elsewhere in Group A. This group includes:	1. Exceeds 12,000 square feet; or
Gymnasiums	2. Has an occupant load of 300 or more; or
Libraries	3. Is located on a floor other than a level of exit discharge serving such occupancies.
Places of religious worship	
Art Galleries	
A-4 Assembly, occupancies intended for viewing of indoor	
sporting events and activities with spectator seating. This	
group includes:	1. Exceeds 12,000 square feet; or
Arenas	2. Has an occupant load of 300 or more; or
Swimming pools	3. Is located on a floor other than a level of exit discharge serving such occupancies.
	An automatic sprinkler system shall be provided for Group A-5 occupancies in the
A-5 Assembly, occupancies intended for participation in or	following areas: concession stands, retail areas, press boxes and other accessory
viewing outdoor activities. This group includes:	use areas in excess of 1,000 square feet.
Bleachers/grandstands	
Stadiums	

Group B (Business) Occupancies: B Business Occupancy includes, among others, the use of a building or structure, or portion thereof, for office, professional or service-type transactions, including storage of records and accounts, such as:	Automatic Fire Sprinkler System Required where:
	1. Four or more care recipients are incapable of self-preservation.
	2. One or more care recipients who are incapable of self-preservation are located
Ambulatory health care facilities	at other than the level of exit discharge serving such an occupancy.
Animal hospitals, kennels and pounds	
Banks	
Barber and beauty shops	
Car wash	
Civic administration	
Clinic - outpatient	
Dry cleaning and laundries: pick-up and delivery station	ons and self-service
Educational occupancies for students above the 12th	grade
Electronic data processing	
Laboratories: testing and research	
Motor vehicle showrooms	
Post offices	
Print shops	
Professional services (architects, attorneys, dentists, physicians, engineers, etc.)	
Radio and television stations	

Group E (Educational) Occupancies: E Educational Occupancy includes, among others, the use of a building or structure, or portion thereof, by six or more persons at any one time for educational purposes throught he 12th grade. Religious educational rooms and religious auditoriums, which are accessory to places of religious worship and have occupant loads of less than 100, shall be classified as A-3 occupancies. <u>Day care.</u> The use of a building or structure, or portion thereof, for educational, supervision or personal care services for more than five children older than 21/2 years of age shall be classified as an E occupancy.	Automatic Fire Sprinkler System Required:
Elementary schools	 Throughout all Group E fire areas greater than 12,000 square fee in area. Throughout every portion of educational buildings below the lowest level of exit
Middle schools	discharge. Exception: An automatic sprinkler system is not required in any area below the
	lowest level of exit discharge serving that area where every classroom throughout
High schools	the building has at least one exterior exit door at ground level.
Day Care	

Group F (Factory Industrial) Occupancies:

Factory Industrial Group F occupancy includes, among others	,
the use of a building or structure, or a potion thereof, for	
assembling, disassembling, fabricating, finishing,	
manufacturing, packaging, repair or processing operations	
that ar enot classified as a Group H hazardous or Group S	
storage occupancy. Factory industrial occupancies are	
classified in Groups F-1 and F-2.	Automatic Fire Sprinkler System Required where:
F-1 Factory Industrial Moderate-hazard, includes occupancies	
which are not classified as Factory Industrial F-2 Low-hazard.	
This group includes:	1. A Group F-1 fire area exceeds 12,000 square feet; or
Appliances	 A group F-1 fire area is located more than three stories above grade plane; or The combined area of all Group F-1 fire areas on all floors, incluidng any mezzanines, exceeds 24,000 squre feet. An automatic sprinkler system shall be provided throughout all Group F-1 occupancy fire areas that contain woodworking operations in excess of 2,500 square feet in area which generate finely divided combustible waste or use finely divided combustible materials.
Bakeries	
Beverages: over 16-percent alcohol content	Food processing
Business machines	Furniture
Carpets and rugs (includes cleaning)	Laundries
Clothing	Machinery
Construction and agricultural machinery	Millwork (sash and door)
Disinfectants	Plastic products
Dry cleaning and dyeing	Printing or publishing
Electric generation plants Electronics	Textiles Upholstering
Engines (including rebuilding)	Woodworking (cabinet)
Ligines (including rebuilding)	

Group F (Factory Industrial) Occupancies, Continued:

F-2 Factory Industrial Low-hazard, includes occupancies that involve the fabrication or manufacturing of noncombustible materials which during finishing, packing or porcessing do not involve a significant fire hazard. This group includes: No requirement for automatic sprinkler systems for this occupancy group. Beverages: up to and inlcuding 16-percent alcolhol content Brick and masonry Ceramic products Foundries Glass products Gypsum Metal products (fabrication and assembly)

Group H (High-Hazard) Occupancies:

High-hazard Group H occupancy includes, among others, the use of a building or structure, or a portion thereof, that involves the manufacturing, processing, generation or storage of materials that constitute a physical or health hazard in quantities in excess of those allowed in control areas (established in the building and fire codes), based on the maximum allowable quantity limits for control areas. Hazardous occupancies are classified in Groups H-1, H-2, H-3, H-4, and H-5.

Automatic Fire Sprinkler System Required:

An automatic sprinkler system shall be installed in Group H occupancies.

Group I (Institutional) Occupancies:

Institutional Group I occupancy includes, among others, the use of a building or structure, or a portion thereof, in which people are cared for or live in a supervised environment, having physical limitations because of health or age are harbored for medical treatment or other care of treatment, or in which people are detained for penal or correctional purposes or in which the liberty of the occupants is restricted. Institutional occupancies shall be classified as Group I-1, I-2, I-3 or I-4.

Automatic Fire Sprinkler System Required:

An automatic sprinkler system shall be provided throughout buildings with a Group I fire area.

Adult care facility Alcohol and drug centers Assisted living facilities Child care facility Congregate care facilities Convalescent facilities **Correctional centers** Detention centers **Detoxification facilities** Group homes Halfway houses Hospitals Jails Mental hospitals **Nursing homes Prerelease centers** Prisons **Reformatories** Residential board and care facilities Social rehabilitation facilities

Group M (Mercantile) Occupancies: Group M Mercantile, includes the use of a building or	
structure or a portion thereof, for the display and sale of	
merchandise and involves stocks of goods, wares or	
merchandise incidental to such purposes and accessible to the	
public. This group includes:	Automatic Fire Sprinkler System Required where:
Department stores	1. A Group M fire area exceeds 12,000 square feet; or
Drug stores	2. A Group M fire area is located more than three stories above grade plane; or
	3. The combined area of all Group M fire areas on all floors, including any
Markets	mezzanines, exceeds 24,000 square feet; or
Motor fuel-dispensing facilities	4. A Group M occupancy is used for the display and sale of upholstered furniture.
	5. An automatic sprinkler system shall be provided in accordance with the
	International Fire Code in all buildings of Group M where storage of merchandise is
Retail or wholesale stores	in high-piled or rack storage arrays.
Sales rooms	

Group R (Residential) Occupancies:

Group R Resiential Occupancy includes the use of a building or structure, or a portion thereof, for sleeping purposes when not classified as an Institutional Group I or when not regulated by the International Residential Code. Residential occupancies shall be classified R-1, R-2, R-3, or R-4. R-1 Residential, includes occupancies containing sleeping units where the occupants are primarily transient in nature. This group includes:	Automatic Fire Sprinkler System Required: An automatic sprinkler system shall be provided throughout all buildings with a Group R fire area.
Boarding houses (transient)	
Hotels (transient)	
Motels (transient)	
Congregate living facilities (transient) with more than	10 occupants
<u>R-2</u> Residential occupancies containing more than two dwelling units or four or more unrelated persons where the occupants are primarily permanent in nature, including:	
	An automatic sprinkler system shall be provided throughout all buildings with a
Apartment houses	Group R fire area.
Boarding houses (nontransient) Dormitories Fraternities and sororities Hotels (nontransient) Live/work units Motels (nontransient) Congregate living facilities (nontransient) with more t	than 16 occupants

Group R (Residential) Occupancies, Continued:	Automatic Fire Sprinkler System Required:
R-3 Residential, includes occupancies where the occupants are primarily permanent in nature and not classified as Group R-1, R-2, R-4 or I. This group includes:	1. An automatic sprinkler system shall be provided throughout all buildings with a Group R fire area.
Adult care facilities that provide accommodations for five or fewer persons of any age for less than 24 hours	2. Adult care and child care facilities that are within a single-family home are premitted to comply with the International Residential Code, and are not required to be provided with automatic sprinkler systems.
Child care facilities that provide accommodations for five or fewer persons of any age for less than 24 hours	Exception: One- and Two-Family Dwellings
Congregate living facilities with 16 or fewer persons	
R-4 Residential, includes buildings arranged for occupancy as residential care/assisted living facilities including five but not more than 16 occupants, excluding staff. An automatic sprinkler system shall be provided throughout all buildings with a Group R fire area. Residential care facilities with between 5 and 16 occupants Assisted living facilities with between 5 and 16 occupants	

Group S (Storage) Occupancies:

Storage Group S occupancy includes, among others, the use of a building or structure, or a portion thereof, for storage that is not classified as a hazardous occupancy. Storage occupancies are classifed as S-1 or S-2. Automatic Fire Sprinkler System Required where: S-1 Storage, moderate-hazard, includes buildings occupied for storage uses that are not classified as S-2. This group includes: 1. A Group S-1 fire area exceeds 12,000 square feet; or Aircraft hangar (storage and repair) 2. A Group S-1 fire area is located more than three stories above grade plane; or **Baskets** Books and paper in rolls or packs 3. the combined area of all Group S-1 fire areas on all floors, including any mezzanines, exceeds 24,000 square feet; or Boots and shoes Cardboard and cardboard boxes 4. A Group S-1 fire area used for the storage of commercial trucks or buses where the fire area exceeds 5,000 square feet. Clothing, woolen wearing apparel Dry boat storage (indoor) Furniture 5. In motor vehicle repair garages, where: a. Buildings having two or more stories above grade plane, including basements, with a fire area containing a repair garage exceeding 10,000 square feet; or Grains b. Buildings no mor ethan one stgory above grade palne, with a fire area containing a repair garage exceeding 12,000 square feet; or Leather c. Buildings with repair garages services vehicles parked in basements; or Lumber d. A Group S-1 fire area used for the repair of commercial trucks or buses where Motor vehicle repair garages the fire area exceeds t,000 square feet. Tires, bulk storage of 6. Buildings and sturctures where the area for the storage of tires exceeds 20,000 **Upholstery and mattresses** cubic feet.

Group S (Storage) Occupancies, Continued:

S-2 Storage, low-hazard, includes buildings used for the storage of noncombustible materials such as producsts on wood pallets or in paper cartons with or without single thickness divisions; or in paper wrappings. Such products are permitted to have a negligible amount of plastic trim, such as knobs, handles or film wrapping. This group includes: Beverages up to and including 16-percent alcolhol in metal, glass or ceramic containers

Cement in bags

Dairy prodcuts in nonwaxed coated paper containers Empty cans

Food products Foods in noncombustible containers Fresh fruits and vegetables in nonplastic trays or containers Frozen foods glass Meats Metals Parking garages, open or enclosed Porcelain and pottery Stoves Washers and dryers

Automatic Fire Sprinkler System Required where:

1. In parking garages (enclosed only):

a. Where the fire area of the enclosed parking garage exceeds 12,000 square feet; or

b. Where the enclosed parking garage is located beneath other groups (except beneath Group R-3 occupancies).

2. Commercial parking garages, throughout buildings used for storage of commercial trucks or buses where the fire area exceeds 5,000 squae feet.

Specific building areas and hazards Stories without openings:	 Automatic Fire Sprinkler System Required where: Throughout all stories, including basements, of all buildings where the floor area exceeds 1,500 square feet and where there is not provided at lesat one of the following types of exterior wall openings: Openings below grade that lead directly to ground level by an exterior building code compliant stairway or ramp. Openings shall be located in each 50 linear feet, or fraction thereof, of exterior wall in the story on at least one side. The required openings shall be distributed such that the lineal distance between adjacent openings does not exceed 50 feet. Openings entirely above the adjoining ground level totaling at least 20 sqyare feet in each linear feet, or fraction thereof, of exterior thereof, of exterior wall in the story on at least one side. The required openings shall be distributed such that the lineal distance between adjacent openings does not exceed 50 feet. Openings entirely above the adjoining ground level totaling at least 20 sqyare feet in each linear feet, or fraction thereof, of exterior wall in the story on at least one side. The required openings shall be distributed such that the lineal distance between adjacent openings does not exceed 50 feet. Openings shall have a minimum dimension of not less than 30 inches. Such openings shall be accessible to the fire department from the exterior and shall not be obstructed in a manner that fire fighting or rescue cannot be accomplished from the exterior. Where openings in a story are provided on only one side and the opposite wall of such story is more than 75 feet from such openings, the story shall be equipped
Rubbish and linen chutes	 throughout with an approved automatic sprinkler system, or openings as specified above shall be provided on at least two sides of the story. 4. Where any portionof a basement is located more than 75 feet from openings as required above, the basement shall be equipped throughout with an approved automatic sprinkler system. An automatic sprinkler system shall be installed at the top of rubbish and linen chutes and in their terminal rooms. Chutes extending through three or more floors shall have additional sprinkler heads installed within such chutes at alternate floors.
Buildings 55 feet or more in height	Chute sprinklers shall be accessible for servicing. An automatic sprinkler system shall be installed throughout buildings with a floor level having an occupant load of 30 or more that is located 55 feet or more above the lowest level of fire department vehicle access.
	Exception 1: Airport control towers. Exception 2: Open parking structures. Exception 3: Occupancies in Group F-2.

Specific building areas and hazards, Continued	Automatic Fire Sprinkler System Required where:
Ducts conveying hazardous exhausts	Where required by the International Mechanical Code, automatic sprinklers shall be provided in ducts conveying hazardous exhuast, or flammable or combustible materials.
	Exception: Ducts in which the largest cross-sectional diamter of the duct is less than 10 inches.
Commercial cooking operations	An automatic sprinkler system shall be installed in commercial kitchen exhaust hood and duct systems where an automatic sprinkler system is used to comply with requirements for automatic fire-extinguishing systems.
Other required suppression systems	In addition to the all of the above provisions additional required suppression systems must be installed in accordance with relevant standards in the following buildings and areas:

Covered malls; High-rise buildings; Atriums; Underground structures; Group I-2; Stages; Special amusement buildings; Aircraft hangars; Group H-2; Flammable finishes; Drying rooms; Unlimited area buildings; Incidental accessory occupancies; Smoke-protected assembly seating; Dry cleaning plants; Dry cleaning machines; Spray finishing in Group A, E, I or R; Spray booths and spray rooms; Dip-tank rooms in Group A, I or R; Dip tanks; Hardening and tempering tanks; HPM facilities; HPM work station exhaust; HPM gas cabinets and exhausted enclosures; HPM exit access corridor; HPM exhaust ducts; Lumber production conveyor enclosures; Class A and B ovens; Class C and D ovens; Hydrogen motor fuel-dispensing area canopies; Storage fire protection (high piled); Storage (high-piled); Gas rooms; Exhausted enclosures; Indoor storage of hazardous materials; Indoor dispensing of hazardous materials; Aerosol warehouses; Aerosol display and merchandising areas; Storage of more than 1,000 cubic feet of loose combustible fibers; Storage of smokeless propellant; Storage of small arms primers; Flammable and combustible liquid storage warehouses; Flammable and combustible liquid Group H-2 or H-3 areas; Gas cabinets for highly toxic and toxic gas; Exhausted enclosures for highly toxic and toxic gas; Pyroxylin plastic storage abinets; Pyroxylin plastic storage and manufacturing; Pyroxylin plastic storage in existing buildings; Existing I-2 occupancies.